



BESTCHEM

Technical Data Sheet

NPP-3000 Anti-migration Paste

Introduction

Anti-migration paste for textile screen printing, excellent anti-migration effect, meets ISO6330, OEKO-TEX requirements.

Specification

- Ingredients: Acrylic Resin
- Appearance: Gray
- Ion: Anion
- Solid Content: $58 \pm 2\%$
- pH: 7-9
- Packing: 30, 50kg PE drum
- Storage: Store air-tight in ventilated area under 35°C, 6 months.

Using suggestion

- Print directly as background to anti-migration.
- Coloring: Mix with PRC series or W series.
- Curing: 120°C, 3 mins or 7 days natural dry before washing.

Remarks

- Products are used for textile printing for water based only; must be stored air-tight after opening to prevent property changes.
- Customer is always recommended to perform test prior to bulk application.
- This TDS is meant as a reference, not a warrantee.
- After six to eight months of storage, please shake well before use. Sediment or oil-water separation is normal. It will not affect or change the quality.

BEST CHEM CO., LTD.

Tel. +886-3-3222667 Email service@chemical.com.tw
No.15, Ln. 192, Sec. 2, Nanshan Rd., Luzhu Dist., Taoyuan City 33860, Taiwan

www.chemical.com.tw