



# BESTCHEM

## Technical Data Sheet

### **NPP-6150 Anti-foil Paste**

#### **Introduction**

- Anti-foil paste for textile screen printing, excellent anti-foil effect, meets ISO6330, OEKO-TEX requirements.
- If yes, please use high fastness of pigment color to avoid the migration problem.
- If anti-foil paste needs to coat on the surface of polyester fabric, it needs to test if this polyester fabric has migration problem.

#### **Specification**

- Appearance: Yellowish
- Ion: Anion
- pH: 8-10
- Packing: 20, 30kg PE drum
- Storage: Store air-tight in ventilated area under 35°C, 6 months.

#### **Using suggestion**

- Apply NPP-6150 Anti-foil paste for the "non-foil" areas (1time, 2 strokes) so that the foil only stick to portions of the image.
- Curing: should leave 2-3 days more to check the effect.

#### **Remarks**

- Products are used for textile printing for water based only; must be stored air-tight after opening to prevent property changes.
- Customer is always recommended to perform test prior to bulk application.
- This TDS is meant as a reference, not a warrantee.
- After six to eight months of storage, please shake well before use. Sediment or oil-water separation is normal. It will not affect or change the quality.

**BEST CHEM CO., LTD.**

Tel. +886-3-3222667 Email [service@chemical.com.tw](mailto:service@chemical.com.tw)  
No.15, Ln. 192, Sec. 2, Nanshan Rd., Luzhu Dist., Taoyuan City 33860, Taiwan

[www.chemical.com.tw](http://www.chemical.com.tw)